Material Safety Data Sheet

Design Concept Series

Version 1

Issue Date 05/21/2021

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: Modeling M200-R001GY General Ink **Recommended use**: UV-radiation curable inks for 3D printers

Manufacturer Information

Company: ApplyLabWork Inc. 3500 Challenger Street Torrance, California 90503 Email: service@applylabwork.com Phone: +1 424 275 4225 Emergency

Service: +1 424 275 4225

2. HAZARDS IDENTIFICATION

Emergency Overview Color: Gray Physical State: Liquid Odor: Slightly acrylic

GHS Labeling

Hazard Pictograms:



Signal Word: Warning

Potential Health Effects

Eye Contact: Cause eye irritation.Skin Contact: Cause skin irritation and allergic skin reactions.Inhalation: Mist of aerosols may cause respiratory irritation.Ingestion: Harmful to health if swallowed.





3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS Number	Weight Percent
Aliphatic Urethane Acrylate Oligomers	Proprietary	Proprietary
Acrylate Monomers	Proprietary	Proprietary
Photoinitiators	Proprietary	Proprietary
Pigment/Dye	Proprietary	Proprietary
4. FIRST AID MEAS	URES	

General Advice: First Aid responders should be aware of wearing protective clothing, including chemical resistant gloves, goggles

Eye Contact: Immediately flush eyes with water for no less than 20 minutes. Consult an ophthalmologist if available. Retract eye contacts while flushing with water

Skin Contact: Use soap and water to remove material from skin immediately. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation persists.

Inhalation: Remove the patient to fresh air. Give artificial respiration if not breathing. Get medical aid when necessary.

Ingestion: Do not induce vomiting. Take plenty of water. If vomiting occurs naturally, have casualty lean forward to reduce the risk of aspiration. Seek medical attention immediately.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Carbon dioxide or dry chemical.

Extinguishing Media to Avoid: Do not use direct water stream.

Hazardous Combustion Products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be irritating.

Unusual Fire and Explosion Hazards: Exposure to light or oxidizers may cause spontaneous polymerization reaction. Under such condition, vapors may be pressurized in closed containers, causing rupture or explosion.

Fire Fighting Procedures: Isolate fire and deny unnecessary entry. Firefighters should wear positivepressure self-contained breathing (SCBA) and protective firefighting clothing (includes firefighting helmet, coat, trousers, boots, and gloves). Avoid contact with this material during firefighting operations.



Personal precautions, protective equipment and emergency procedures: Isolate area. Keep unnecessary and unprotected personnel from entering the area. Use appropriate safety equipment. For additional information, refer to Section 8.

Environmental Precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological information.

Methods and Materials for Containment and Cleaning Up: Contain spilled material if possible. Absorb with materials such as sand, polypropylene/polyethylene fiber products. Use non-sparking shovels to remove material. Collect in suitable and properly labeled containers.

7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation. Avoid prolonged or repeated contact with skin. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Avoid breathing dust/fume/gas/mist/vapors/sprays. Avoid use of electric band heaters.

Storage: Keep container tightly closed. Store in a dry, cool and well-ventilated place and avoid direct sun light exposure. Keep product and empty container away from heat and sources of ignition. Take measures to prevent the buildup of electrostatic charge. Use within 24 months and store the containers at 10-30 °C (55-86 °F).

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits: No exposure guidelines available for components in this product.

Personal Protection

Eye/Face Protection: Wear safety glasses with side shields or goggles to protect against splashing. **Skin Protection**: Use protective clothing chemically resistant to this material. Wear neoprene or nitrile impervious gloves. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task. **Respiratory Protection**: For most conditions, no respiratory protection should be needed. However, if material is heated or sprayed, use respirators. Respirators of organic vapor cartridge with a particulate pre-filter may be suitable.

Engineering Controls: Use local exhaust ventilation. General ventilation should be sufficient for most operations.

9. PHYSCIAL AND CHEMICAL PROPERTIES

Appearance: Gray Liquid pH: Not applicable Odor: Slightly acrylic Melting Point: Not applicable Boiling Point: Not applicable

Freezing Point: Not applicable

Flash point: > 100 °C

Page 3 of 6

Upper Explosion Limit: No Data	Lower Explosion Limit: No Data
Specific Gravity: 1.08-1.15	Viscosity : 100-3,000 cps @ 25° C(77° F)
Vapor Pressure: No Data	Evaporation Rate (Butyl acrylate = 1): No Data
Auto Ignition Temperature: Not applicable	Partition Coefficient (n-octanol/water): No Data

10. STABILITY AND REACTIVITY

Stability: Stable under recommended storage conditions. See Section 7.

Chemical Stability: Avoid exposure to heat, light and incompatible materials.

Incompatible Materials: Avoid contact with oxidizing materials, peroxides, acids, bases and fine metal powders.

Possibility of Hazardous Reactions: Polymerization may occur with considerable buildup of heat and pressure

Hazardous Decomposition Products: Decomposition reaction would generate carbon oxides, nitrogen oxides, and fragments of organic compounds.

11. TOXICOLOGICAL INFORMATION

General Information

Likely routes of exposures and symptoms: See Section 2.

Acute Toxicity

Product: No data available Components:

Oral LD50	Dermal LD50
Acrylate Monomers Rats, 6200 mg/Kg (vendor literature)	Rabbits > 2000 mg/Kg (vendor literature)

Aliphatic Urethane Acrylate Oligomer Not available Not available

Carcinogenicity: None of components in this product are classified as carcinogens

Reproductive Toxicity: Contain small amount of such substance (photoinitiator).

12. ECOLOGICAL INFORMATION

Ecotoxicity

The product is moderately toxic to aquatic organisms and not allowed to drain into sewers and waterways **Persistence and Degradability**



Biodegradability: Not biodegradable. Bioaccumulation: No data available Mobility in soil No data available

13. DISPOSAL CONSIDERATIONS

14. TRANSPORT INFORMATION

Do not dump into any sewers, on the ground, or into any body of water. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations.

For unused product, the preferred options include sending to a licensed, permitted incinerator or other thermal destruction device. For product residue in packing containers, expose residue under sun light and dispose.

		-	
US DOT	IATA	IMDG	Canada TDG

Shipping Name	Not Regulated	
Hazard Class	Not Regulated	
UN Number	Not Regulated	
Packing Group	Not Regulated	
15. REGULATORY INFORMATION		

_	TSCA	EINECS	DSL	NDSL
Acrylate Oligomers	Yes	Yes	Yes	No
Acrylate Monomers	Yes	Yes	Yes	No
Photoinitiator(s)	Yes	Yes	Yes	No

Components of the product are examined with TSCA inventory, online EC inventory and DSL website search engine. Components of greater than 0.1% by weight are listed above.

US Federal	
Regulation	Components
SARA Section 302 (40 CFR 355)	Not Listed
SARA Section 313 (40 CFR 372.65)	Not Listed
CERCLA (40 CFR 302.4)	Not Listed
California Proposition 65	Not Listed
16. OTHER INFORMATION	

Hazardous Materials Identification System (HMIS)



Health:2Flammability:1Physical Hazards:1(Degree of hazard: 0 = low, 4 = extreme)

Disclaimer

To the best of our knowledge, the information provided in this (M)SDS sheet is believed to be correct. No guarantee or warranty of any kind, expressed or implied, is made with respect to such data or information. Regulatory requirements are subject to change and may differ between various locations. Users are responsible to ensure that his activities comply with all federal, state, provincial or local laws.

