

Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 24

LOCTITE 3D 5015 A80 Elastomeric White

SDS No. : 646002 V004.0 Revision: 01.12.2022 printing date: 22.03.2023 Replaces version from: 25.01.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE 3D 5015 A80 Elastomeric White

1.2. Relevant identified uses of the substance or mixture and uses advised against Intended use: Adhesive/Sealant

1.3. Details of the supplier of the safety data sheet

Henkel Ltd Adhesives Wood Lane End HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website https://mysds.henkel.com/index.html#/appSelection or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin irritation	Category 2
H315 Causes skin irritation.	
Skin sensitizer	Category 1
H317 May cause an allergic skin reaction.	
Serious eye irritation	Category 2
H319 Causes serious eye irritation.	
Specific target organ toxicity - single exposure	Category 3
H335 May cause respiratory irritation.	
Target organ: respiratory tract irritation	
Acute hazards to the aquatic environment	Category 1
H400 Very toxic to aquatic life.	
Chronic hazards to the aquatic environment	Category 1
H410 Very toxic to aquatic life with long lasting effects.	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:	
Contains	Isobornyl acrylate
	Dicyclopentyldimethylene diacrylate Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate
Signal word:	Warning
Hazard statement:	 H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H410 Very toxic to aquatic life with long lasting effects.
Precautionary statement: Prevention	P261 Avoid breathing vapors.P273 Avoid release to the environment.P280 Wear protective gloves.
Precautionary statement: Response	P302+P352 IF ON SKIN: Wash with plenty of soap and water. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

None if used properly.

This mixture contains components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB).

Following substances are present in a concentration \geq the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

PBT/vPvB
PBT/vPvB

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M- factors and ATEs	Add. Information
Isobornyl acrylate 5888-33-5 227-561-6 01-2119957862-25	25- 50 %	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M acute = 1 M chronic = 1	
Dicyclopentyldimethylene diacrylate 42594-17-2 255-901-3 01-2120051112-76	0,1-< 1 %	Skin Sens. 1B, H317 Aquatic Chronic 2, H411		
Ethyl phenyl(2,4,6- trimethylbenzoyl)phosphinate 84434-11-7 282-810-6 01-2119987994-10	0,1-< 1 %	Aquatic Chronic 2, H411 Skin Sens. 1B, H317		
Phenyl bis(2,4,6- trimethylbenzoyl)-phosphine oxide 162881-26-7 423-340-5 01-2119489401-38 01-2119936813-33	0,1-< 1 %	Skin Sens. 1A, H317 Aquatic Chronic 4, H413		
Camphene 79-92-5 201-234-8	0,1-< 1 %	Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Flam. Sol. 2, H228 Eye Irrit. 2, H319	M acute = 1 M chronic = 1	
1,7,7- Trimethyltricyclo[2.2.1.02,6]hept ane 508-32-7 208-083-7, 208-083-7	0,1-< 1 %	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M acute = 1 M chronic = 1	
Titanium dioxide 13463-67-7 236-675-5 01-2119489379-17	0,1-< 1 %	Carc. 2, Inhalation, H351		
Dodecamethylcyclohexasiloxane 540-97-6 208-762-8 01-2119517435-42	0,1-< 1 %	Aquatic Chronic 4, H413		SVHC PBT/vPvB
Ethanone, 2,2-dimethoxy-1,2- diphenyl- 24650-42-8 246-386-6 01-2120000336-73	0,1-< 1 %	Aquatic Chronic 1, H410 Aquatic Acute 1, H400	M acute = 1 M chronic = 1	
octamethylcyclotetrasiloxane 556-67-2 209-136-7 01-2119529238-36	0,01-< 0,1 %	Aquatic Chronic 1, H410 Repr. 2, H361f Flam. Liq. 3, H226	M chronic = 10	SVHC PBT/vPvB

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

Skin contact: Rinse with running water and soap. Obtain medical attention if irritation persists.

Eye contact: Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion: Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed EYE: Irritation, conjunctivitis.

SKIN: Redness, inflammation.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

SKIN: Rash, Urticaria.

4.3. Indication of any immediate medical attention and special treatment needed See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons: High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released. Silicon dioxide

5.3. Advice for firefighters Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information: In case of fire, keep containers cool with water spray.

SECTION 6: Accidental r	release	measure	es
--------------------------------	---------	---------	----

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Wear protective equipment. Ensure adequate ventilation.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13. For small spills wipe up with paper towel and place in container for disposal. For large spills absorb onto inert absorbent material and place in sealed container for disposal.

6.4. Reference to other sections

See advice in section 8

7.1. Precautions for safe handling

Avoid skin and eye contact. See advice in section 8

Hygiene measures:

Wash hands before work breaks and after finishing work. Do not eat, drink or smoke while working. Good industrial hygiene practices should be observed.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction. Keep container tightly sealed. Refer to Technical Data Sheet

7.3. Specific end use(s)

Adhesive/Sealant

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³			Regulatory list
				category / Remarks	
Titanium dioxide		4	Time Weighted Average		EH40 WEL
13463-67-7			(TWA):		
[TITANIUM DIOXIDE, RESPIRABLE]					
Titanium dioxide		10	Time Weighted Average		EH40 WEL
13463-67-7			(TWA):		
[TITANIUM DIOXIDE, TOTAL					
INHALABLE]					

Occupational Exposure Limits

Valid for Ireland

Ingredient [Regulated substance] Short term exposure limit **Regulatory list** ppm mg/m³ Value type category / Remarks Titanium dioxide 10 Time Weighted Average IR_OEL 13463-67-7 (TWA): [TITANIUM DIOXIDE] 4 Time Weighted Average IR_OEL Titanium dioxide 13463-67-7 (TWA): [TITANIUM DIOXIDE]

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental		Value				Remarks
	Compartment	period					
T 1 1 1 .			mg/l	ppm	mg/kg	others	
Isobornyl acrylate 5888-33-5	aqua (freshwater)		0,001 mg/l				
Isobornyl acrylate	aqua		0,007 mg/l				
5888-33-5	(intermittent						
	releases)						
Isobornyl acrylate	aqua (marine		0,0001				
5888-33-5	water)		mg/l				
Isobornyl acrylate 5888-33-5	sewage treatment plant		2 mg/l				
2000-22-2	(STP)						
Isobornyl acrylate	sediment				0,145		
5888-33-5	(freshwater)				mg/kg		
Isobornyl acrylate	sediment				0,0145		
5888-33-5	(marine water)				mg/kg		
Isobornyl acrylate	Soil				0,0285		
5888-33-5	D. L.				mg/kg		
Isobornyl acrylate 5888-33-5	Predator						no potential for bioaccumulation
(Octahydro-4,7-methano-1H-	aqua		0,0016				
indenediyl)bis(methylene) diacrylate	(freshwater)		mg/l				
42594-17-2	` ´		C				
(Octahydro-4,7-methano-1H-	aqua (marine		0,00016				
indenediyl)bis(methylene) diacrylate	water)		mg/l				
42594-17-2 (Octahydro-4,7-methano-1H-	and in such		-		0.6576		
(Octahydro-4, /-methano-1H- indenediyl)bis(methylene) diacrylate	sediment (freshwater)				0,6576 mg/kg		
42594-17-2	(ITESITWATEL)				mg/kg		
(Octahydro-4,7-methano-1H-	sediment				0,0658		
indenediyl)bis(methylene) diacrylate	(marine water)				mg/kg		
42594-17-2							
(Octahydro-4,7-methano-1H-	Soil				0,1306		
indenediyl)bis(methylene) diacrylate					mg/kg		
42594-17-2 (Octahydro-4,7-methano-1H-			10				
indenediyl)bis(methylene) diacrylate	sewage treatment plant		10 mg/l				
42594-17-2	(STP)						
(Octahydro-4,7-methano-1H-	aqua		0,016 mg/l				
indenediyl)bis(methylene) diacrylate	(intermittent						
42594-17-2	releases)						
Ethyl phenyl(2,4,6-	aqua		0,00101				
trimethylbenzoyl)phosphinate 84434-11-7	(freshwater)		mg/l				
Ethyl phenyl(2,4,6-	aqua (marine		0,000101				
trimethylbenzoyl)phosphinate	water)		mg/l				
84434-11-7							
Ethyl phenyl(2,4,6-	aqua		0,035 mg/l				
trimethylbenzoyl)phosphinate	(intermittent						
84434-11-7 Ethyl phenyl(2,4,6-	releases) sediment				0,24 mg/kg		
trimethylbenzoyl)phosphinate	(freshwater)				0,24 mg/kg		
84434-11-7	(,						
Ethyl phenyl(2,4,6-	sediment				0,024		
trimethylbenzoyl)phosphinate	(marine water)				mg/kg		
84434-11-7	C - :1				0.047		
Ethyl phenyl(2,4,6- trimethylbenzoyl)phosphinate	Soil				0,047 mg/kg		
84434-11-7	1				mg/kg		
Phenyl bis(2,4,6-trimethylbenzoyl)-	aqua		0,001 mg/l				
phosphine oxide	(freshwater)						
162881-26-7		ļ		ļ		ļ	
Phenyl bis(2,4,6-trimethylbenzoyl)-	aqua		0,001 mg/l				
phosphine oxide 162881-26-7	(intermittent releases)						
Phenyl bis(2,4,6-trimethylbenzoyl)-	aqua (marine		0,001 mg/l				
phosphine oxide	water)		0,001 mg/1				
162881-26-7	ĺ ĺ						
Phenyl bis(2,4,6-trimethylbenzoyl)-	sewage		1 mg/l				
phosphine oxide	treatment plant						
162881-26-7	(STP)				0.712		
Phenyl bis(2,4,6-trimethylbenzoyl)-	sediment			L	0,712		

phosphine oxide 162881-26-7	(freshwater)		mg/kg	
Phenyl bis(2,4,6-trimethylbenzoyl)- phosphine oxide 162881-26-7	sediment (marine water)		0,712 mg/kg	
Phenyl bis(2,4,6-trimethylbenzoyl)- phosphine oxide 162881-26-7	Soil		20 mg/kg	
Dodecamethylcyclohexasiloxane 540-97-6	sediment (freshwater)		13,5 mg/kg	
Dodecamethylcyclohexasiloxane 540-97-6	oral		66,7 mg/kg	
Dodecamethylcyclohexasiloxane 540-97-6	sediment (marine water)		1,35 mg/kg	
2,2-Dimethoxy-1,2-diphenylethan-1-one 24650-42-8	aqua (freshwater)	0,229 mg/l		
2,2-Dimethoxy-1,2-diphenylethan-1-one 24650-42-8	Freshwater - intermittent	0,184 mg/l		
2,2-Dimethoxy-1,2-diphenylethan-1-one 24650-42-8	aqua (marine water)	0,0229 mg/l		
2,2-Dimethoxy-1,2-diphenylethan-1-one 24650-42-8	sewage treatment plant (STP)	19,4 mg/l		
2,2-Dimethoxy-1,2-diphenylethan-1-one 24650-42-8	sediment (freshwater)		8,87 mg/kg	
2,2-Dimethoxy-1,2-diphenylethan-1-one 24650-42-8	sediment (marine water)		0,887 mg/kg	
2,2-Dimethoxy-1,2-diphenylethan-1-one 24650-42-8	Soil		1,64 mg/kg	
Octamethylcyclotetrasiloxane 556-67-2	aqua (freshwater)	0,0015 mg/l		
Octamethylcyclotetrasiloxane 556-67-2	aqua (marine water)	0,00015 mg/l		
Octamethylcyclotetrasiloxane 556-67-2	sewage treatment plant (STP)	10 mg/l		
Octamethylcyclotetrasiloxane 556-67-2	sediment (freshwater)		3 mg/kg	
Octamethylcyclotetrasiloxane 556-67-2	sediment (marine water)		0,3 mg/kg	
Octamethylcyclotetrasiloxane 556-67-2	oral		41 mg/kg	
Octamethylcyclotetrasiloxane 556-67-2	Soil		0,54 mg/kg	

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Isobornyl acrylate 5888-33-5	Workers	dermal	Long term exposure - systemic effects		1,39 mg/kg	no potential for bioaccumulation
Isobornyl acrylate 5888-33-5	General population	oral	Long term exposure - systemic effects		0,83 mg/kg	no potential for bioaccumulation
Isobornyl acrylate 5888-33-5	General population	dermal	Long term exposure - systemic effects		0,83 mg/kg	no potential for bioaccumulation
Ethyl phenyl(2,4,6- trimethylbenzoyl)phosphinate 84434-11-7	Workers	dermal	Long term exposure - systemic effects		1,7 mg/kg	
Ethyl phenyl(2,4,6- trimethylbenzoyl)phosphinate 84434-11-7	Workers	inhalation	Long term exposure - systemic effects		5,88 mg/m3	
Ethyl phenyl(2,4,6- trimethylbenzoyl)phosphinate 84434-11-7	General population	inhalation	Long term exposure - systemic effects		0,87 mg/m3	
Ethyl phenyl(2,4,6- trimethylbenzoyl)phosphinate 84434-11-7	General population	dermal	Long term exposure - systemic effects		0,5 mg/kg	
Ethyl phenyl(2,4,6- trimethylbenzoyl)phosphinate 84434-11-7	General population	oral	Long term exposure - systemic effects		0,5 mg/kg	
Phenyl bis(2,4,6-trimethylbenzoyl)- phosphine oxide 162881-26-7	Workers	Inhalation	Long term exposure - systemic effects		21 mg/m3	
Phenyl bis(2,4,6-trimethylbenzoyl)- phosphine oxide 162881-26-7	Workers	dermal	Long term exposure - systemic effects		3 mg/kg	
Phenyl bis(2,4,6-trimethylbenzoyl)- phosphine oxide 162881-26-7	General population	inhalation	Long term exposure - systemic effects		5,2 mg/m3	
Phenyl bis(2,4,6-trimethylbenzoyl)- phosphine oxide 162881-26-7	General population	dermal	Long term exposure - systemic effects		1,5 mg/kg	
Phenyl bis(2,4,6-trimethylbenzoyl)- phosphine oxide 162881-26-7	General population	oral	Long term exposure - systemic effects		1,5 mg/kg	
Titanium dioxide 13463-67-7	Workers	inhalation	Long term exposure - local effects		0,17 mg/m3	
Titanium dioxide 13463-67-7	General population	inhalation	Long term exposure - local effects		0,028 mg/m3	
Dodecamethylcyclohexasiloxane 540-97-6	Workers	inhalation	Long term exposure - local effects		1,22 mg/m3	
Dodecamethylcyclohexasiloxane 540-97-6	Workers	inhalation	Acute/short term exposure - local effects		6,1 mg/m3	
Dodecamethylcyclohexasiloxane 540-97-6	General population	inhalation	Long term exposure - local effects		0,3 mg/m3	
Dodecamethylcyclohexasiloxane 540-97-6	General population	inhalation	Acute/short term exposure - local effects		1,5 mg/m3	
2,2-Dimethoxy-1,2-diphenylethan-1-one 24650-42-8	Workers	inhalation	Long term exposure - systemic effects		2,11 mg/m3	
2,2-Dimethoxy-1,2-diphenylethan-1-one 24650-42-8	Workers	dermal	Long term exposure - systemic effects		0,599 mg/kg	
2,2-Dimethoxy-1,2-diphenylethan-1-one 24650-42-8	General population	inhalation	Long term exposure - systemic effects		0,372 mg/m3	
2,2-Dimethoxy-1,2-diphenylethan-1-one 24650-42-8	General population	dermal	Long term exposure - systemic effects		0,214 mg/kg	
2,2-Dimethoxy-1,2-diphenylethan-1-one 24650-42-8	General population	oral	Long term exposure -		0,214 mg/kg	

		1	systemic effects		
Octamethylcyclotetrasiloxane 556-67-2	Workers	inhalation	Long term exposure - systemic effects	73 mg/m3	
Octamethylcyclotetrasiloxane 556-67-2	Workers	inhalation	Long term exposure - local effects	73 mg/m3	
Octamethylcyclotetrasiloxane 556-67-2	General population	inhalation	Long term exposure - systemic effects	13 mg/m3	
Octamethylcyclotetrasiloxane 556-67-2	General population	inhalation	Long term exposure - local effects	13 mg/m3	
Octamethylcyclotetrasiloxane 556-67-2	General population	oral	Long term exposure - systemic effects	3,7 mg/kg	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls: Ensure good ventilation/extraction.

Respiratory protection: Ensure adequate ventilation. An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area Filter type: A (EN 14387)

Hand protection: Chemical-resistant protective gloves (EN 374). Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374): nitrile rubber (NBR; >= 0.4 mm thickness) Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): nitrile rubber (NBR; >= 0.4 mm thickness) This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g.

Eye protection: Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing. Protective eye equipment should conform to EN166.

Skin protection: Wear suitable protective clothing. Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	liquid
Delivery form	liquid
Colour	white

Odor	Acrylic
Melting point	Not applicable, Product is a liquid
Solidification temperature	<0 °C (< 32 °F)
Initial boiling point	> 149 °C (> 300.2 °F)
Flammability	The product is not flammable.
Explosive limits	Not applicable, The product is not flammable.
Flash point	> 93 °C (> 199.4 °F)
Auto-ignition temperature	Not applicable, The product is not flammable.
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use
all	
pH Viscosity (hinematic)	Not applicable, Product is non-soluble (in water). > 20,5 mm2/s
Viscosity (kinematic) (40 °C (104 °F);)	> 20,3 mm2/8
	prostically insoluble
Solubility (qualitative) (20 °C (68 °F); Solvent: Water)	practically insoluble
Partition coefficient: n-octanol/water	Not applicable
Tartition coefficient. n-octanol/ water	Mixture
Vapour pressure	< 1.3 kPa
$(20 \ ^{\circ}C \ (68 \ ^{\circ}F))$	< 1,5 M a
Density	0,96 - 1,0 g/cm3
(20 °C (68 °F))	0,20 1,0 <u>9</u> ,0112
Relative vapour density:	>1
(20 °C)	
Particle characteristics	Not applicable
	Product is a liquid
	-

9.2. Other information Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity Reacts with oxidants, acids and lyes

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use. Excessive heat.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

None if used for intended purpose.

SECTION 11: Toxicological information

1.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Isobornyl acrylate 5888-33-5	LD50	4.350 mg/kg	rat	not specified
Dicyclopentyldimethylene diacrylate 42594-17-2	LD50	> 2.000 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
Ethyl phenyl(2,4,6- trimethylbenzoyl)phosphi nate 84434-11-7	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Phenyl bis(2,4,6- trimethylbenzoyl)- phosphine oxide 162881-26-7	LD50	> 2.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Camphene 79-92-5	LD50	>= 5.000 mg/kg	rat	Limit Test
Titanium dioxide 13463-67-7	LD50	> 5.000 mg/kg	rat	OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)
Dodecamethylcyclohexasi loxane 540-97-6	LD50	> 2.000 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
Ethanone, 2,2-dimethoxy- 1,2-diphenyl- 24650-42-8	LD50	> 5.000 mg/kg	rat	not specified
octamethylcyclotetrasilox ane 556-67-2	LD50	> 4.800 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Isobornyl acrylate 5888-33-5	LD50	> 3.000 mg/kg	rabbit	not specified
Dicyclopentyldimethylene diacrylate 42594-17-2	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Ethyl phenyl(2,4,6- trimethylbenzoyl)phosphi nate 84434-11-7	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Phenyl bis(2,4,6- trimethylbenzoyl)- phosphine oxide 162881-26-7	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Titanium dioxide 13463-67-7	LD50	> 10.000 mg/kg	rabbit	not specified
Dodecamethylcyclohexasi loxane 540-97-6	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Ethanone, 2,2-dimethoxy- 1,2-diphenyl- 24650-42-8	LD50	> 5.000 mg/kg	rat	not specified
octamethylcyclotetrasilox ane 556-67-2	LD50	> 2.375 mg/kg	rat	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Titanium dioxide 13463-67-7	LC50	> 6,82 mg/l	dust	4 h	rat	not specified
octamethylcyclotetrasilox ane 556-67-2	LC50	36 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Result	Exposure	Species	Method
CAS-No.		time		
Isobornyl acrylate 5888-33-5	irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Dicyclopentyldimethylene diacrylate 42594-17-2	not irritating		In vitro	OECD Guideline 439 (In Vitro Skin Irritation: Reconstructed Human Epidermis (RHE) Test Method)
Camphene 79-92-5	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Titanium dioxide 13463-67-7	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Dodecamethylcyclohexasi loxane 540-97-6	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
octamethylcyclotetrasilox ane 556-67-2	not irritating		rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Dicyclopentyldimethylene diacrylate 42594-17-2	not irritating		In vitro	OECD Guideline 437 (BCOP)
Camphene 79-92-5	irritating	24 h	rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Titanium dioxide 13463-67-7	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Dodecamethylcyclohexasi loxane 540-97-6	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
octamethylcyclotetrasilox ane 556-67-2	not irritating		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Isobornyl acrylate 5888-33-5	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Dicyclopentyldimethylene diacrylate 42594-17-2	Sub-Category 1B (sensitising)	Freund's complete adjuvant test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Ethyl phenyl(2,4,6- trimethylbenzoyl)phosphi nate 84434-11-7	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Titanium dioxide 13463-67-7	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Titanium dioxide 13463-67-7	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Dodecamethylcyclohexasi loxane 540-97-6	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
octamethylcyclotetrasilox ane 556-67-2	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result	Type of study /	Metabolic	Species	Method
CAS-No.		Route of administration	activation / Exposure time		
Isobornyl acrylate 5888-33-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Isobornyl acrylate 5888-33-5	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Isobornyl acrylate 5888-33-5	negative	in vitro mammalian cell micronucleus test	with and without		OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
Dicyclopentyldimethylene diacrylate 42594-17-2	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Titanium dioxide 13463-67-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Titanium dioxide 13463-67-7	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Titanium dioxide 13463-67-7	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Titanium dioxide 13463-67-7	negative	in vitro mammalian cell micronucleus test	without		equivalent or similar to OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
Dodecamethylcyclohexasi loxane 540-97-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Dodecamethylcyclohexasi loxane 540-97-6	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
octamethylcyclotetrasilox ane 556-67-2	negative	bacterial gene mutation assay	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
octamethylcyclotetrasilox ane 556-67-2	negative	in vitro mammalian chromosome aberration test	with and without		equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
octamethylcyclotetrasilox ane 556-67-2	negative	mammalian cell gene mutation assay	with and without		equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Camphene 79-92-5	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Titanium dioxide 13463-67-7	negative	oral: gavage		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Dodecamethylcyclohexasi loxane 540-97-6	negative	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
octamethylcyclotetrasilox ane 556-67-2	negative	inhalation		rat	equivalent or similar to OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test)
octamethylcyclotetrasilox ane 556-67-2	negative	oral: gavage		rat	equivalent or similar to OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Titanium dioxide 13463-67-7	not carcinogenic	oral: feed	103 w daily	rat	male/female	not specified

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Isobornyl acrylate 5888-33-5	NOAEL P 100 mg/kg NOAEL F1 100 mg/kg	screening	oral: gavage	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Titanium dioxide 13463-67-7	NOAEL P >= 1.000 mg/kg NOAEL F1 >= 1.000 mg/kg	one- generation study	oral: feed	rat	OECD Guideline 443 (Extended One-Generation Reproductive Toxicity Study)
Dodecamethylcyclohexasi loxane 540-97-6	NOAEL P 1.000 mg/kg NOAEL F1 1.000 mg/kg	screening	oral: gavage	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
octamethylcyclotetrasilox ane 556-67-2	NOAEL P 300 ppm NOAEL F1 300 ppm	two- generation study	inhalation	rat	equivalent or similar to OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Isobornyl acrylate 5888-33-5	NOAEL 100 mg/kg	oral: gavage	once daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Dicyclopentyldimethylene diacrylate 42594-17-2	NOAEL 1.000 mg/kg	oral: gavage		rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
Camphene 79-92-5	LOAEL 1.000 mg/kg	oral: gavage	28 days daily	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
Titanium dioxide 13463-67-7	NOAEL > 1.000 mg/kg	oral: gavage	92 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Dodecamethylcyclohexasi loxane 540-97-6	NOAEL 1.000 mg/kg	oral: gavage	29 d daily, 7 d/w	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
octamethylcyclotetrasilox ane 556-67-2	LOAEL 35 ppm	inhalation	6 h nose only inhalation 5 days/week for 13 weeks	rat	OECD Guideline 412 (Repeated Dose Inhalation Toxicity: 28/14-Day)
octamethylcyclotetrasilox ane 556-67-2	NOAEL 960 mg/kg	dermal	3 w 5 d/w	rabbit	equivalent or similar to OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type		_		
Isobornyl acrylate	LC50	0,704 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish,
5888-33-5					Acute Toxicity Test)
Dicyclopentyldimethylene	LC50	1,65 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish,
diacrylate					Acute Toxicity Test)
42594-17-2					
Ethyl phenyl(2,4,6-	LC50	1,89 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish,
trimethylbenzoyl)phosphinate					Acute Toxicity Test)
84434-11-7					
Phenyl bis(2,4,6-	LC50	Toxicity > Water	96 h	Danio rerio	OECD Guideline 203 (Fish,
trimethylbenzoyl)-phosphine		solubility'			Acute Toxicity Test)
oxide					
162881-26-7					
Camphene	LC50	0,72 mg/l	96 h	Brachydanio rerio (new name:	OECD Guideline 203 (Fish,
79-92-5				Danio rerio)	Acute Toxicity Test)
Titanium dioxide	LC50	Toxicity > Water	48 h	Leuciscus idus	OECD Guideline 203 (Fish,
13463-67-7		solubility			Acute Toxicity Test)
Dodecamethylcyclohexasiloxa	NOEC	Toxicity > Water	90 d	Oncorhynchus mykiss	OECD Guideline 210 (fish
ne		solubility			early lite stage toxicity test)
540-97-6					
Ethanone, 2,2-dimethoxy-1,2-	LC50	7,2 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish,
diphenyl-					Acute Toxicity Test)
24650-42-8					
octamethylcyclotetrasiloxane	NOEC	0,0044 mg/l	93 d	Salmo gairdneri (new name:	EPA OPPTS 797.1600 (Fish
556-67-2				Oncorhynchus mykiss)	Early Life Stage Toxicity
					Test)
octamethylcyclotetrasiloxane	LC50	Toxicity > Water	96 h	Oncorhynchus mykiss	EPA OTS 797.1400 (Fish
556-67-2		solubility			Acute Toxicity Test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Isobornyl acrylate 5888-33-5	EC50	1 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute
					Immobilisation Test)
Dicyclopentyldimethylene diacrylate	EC50	2,36 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute
42594-17-2					Immobilisation Test)
Ethyl phenyl(2,4,6-	EC50	2,26 mg/l	48 h	Daphnia magna	OECD Guideline 202
trimethylbenzoyl)phosphinate 84434-11-7					(Daphnia sp. Acute Immobilisation Test)
Phenyl bis(2,4,6-	EC50	Toxicity > Water	48 h	Daphnia magna	OECD Guideline 202
trimethylbenzoyl)-phosphine oxide		solubility			(Daphnia sp. Acute Immobilisation Test)
162881-26-7					,
Camphene 79-92-5	EC50	22 mg/l	48 h	Daphnia magna	OECD Guideline 202
19-92-5					(Daphnia sp. Acute Immobilisation Test)
Titanium dioxide	EC50	Toxicity > Water	48 h	Daphnia magna	OECD Guideline 202
13463-67-7		solubility			(Daphnia sp. Acute Immobilisation Test)
Ethanone, 2,2-dimethoxy-1,2-	EC50	26 mg/l	24 h	Daphnia magna	OECD Guideline 202
diphenyl-		-			(Daphnia sp. Acute
24650-42-8	5050		40.1	D 1 '	Immobilisation Test)
octamethylcyclotetrasiloxane	EC50	Toxicity > Water	48 h	Daphnia magna	EPA OTS 797.1300
556-67-2		solubility			(Aquatic Invertebrate Acute
					Toxicity Test, Freshwater
				l	Daphnids)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type		_		
Isobornyl acrylate	NOEC	0,092 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia
5888-33-5					magna, Reproduction Test)
Phenyl bis(2,4,6-	NOEC	Toxicity > Water	21 day	Daphnia magna	OECD 211 (Daphnia
trimethylbenzoyl)-phosphine		solubility			magna, Reproduction Test)
oxide					
162881-26-7					
Titanium dioxide	NOEC	Toxicity > Water	21 d	Daphnia magna	OECD Guideline 202
13463-67-7		solubility			(Daphnia sp. Chronic
					Immobilisation Test)
Dodecamethylcyclohexasiloxa	NOEC	Toxicity > Water	21 d	Daphnia magna	OECD 211 (Daphnia
ne		solubility			magna, Reproduction Test)
540-97-6					
octamethylcyclotetrasiloxane	NOEC	7.9 μg/l	21 d	Daphnia magna	EPA OTS 797.1330
556-67-2					(Daphnid Chronic Toxicity
					Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.
--

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Isobornyl acrylate 5888-33-5	NOEC	0,405 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Isobornyl acrylate 5888-33-5	EC50	1,98 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Dicyclopentyldimethylene diacrylate 42594-17-2	EC50	1,6 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Dicyclopentyldimethylene diacrylate 42594-17-2	EC10	0,64 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Ethyl phenyl(2,4,6- trimethylbenzoyl)phosphinate 84434-11-7	EC50	1,01 mg/l	72 h	Desmodesmus subspicatus	not specified
Phenyl bis(2,4,6- trimethylbenzoyl)-phosphine oxide 162881-26-7	EC50	Toxicity > Water solubility	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Phenyl bis(2,4,6- trimethylbenzoyl)-phosphine oxide 162881-26-7	NOEC	Toxicity > Water solubility	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Camphene 79-92-5	NOEC	320 - 580 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Camphene 79-92-5	EC50	> 1.000 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Titanium dioxide 13463-67-7	EC50	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Titanium dioxide 13463-67-7	NOEC	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Dodecamethylcyclohexasiloxa ne 540-97-6	NOEC	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Dodecamethylcyclohexasiloxa ne 540-97-6	EC50	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Ethanone, 2,2-dimethoxy-1,2- diphenyl- 24650-42-8	EC50	0,17 mg/l	72 h	Scenedesmus sp.	OECD Guideline 201 (Alga, Growth Inhibition Test)
octamethylcyclotetrasiloxane 556-67-2	EC50	Toxicity > Water solubility	96 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	-
octamethylcyclotetrasiloxane 556-67-2	EC10	0,022 mg/l	96 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	EPA OTS 797.1050 (Algal Toxicity, Tiers I and II)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Phenyl bis(2,4,6-	EC 50	> 100 mg/l	3 h		OECD Guideline 209
trimethylbenzoyl)-phosphine					(Activated Sludge,
oxide					Respiration Inhibition Test)
162881-26-7					
Camphene	EC10	490 mg/l	3 h		OECD Guideline 209
79-92-5					(Activated Sludge,
					Respiration Inhibition Test)
Titanium dioxide	EC0	Toxicity > Water	24 h	Pseudomonas fluorescens	DIN 38412, part 8
13463-67-7		solubility			(Pseudomonas
					Zellvermehrungshemm-
					Test)
Ethanone, 2,2-dimethoxy-1,2-	EC 50	> 100 mg/l	3 h		OECD Guideline 209
diphenyl-					(Activated Sludge,
24650-42-8					Respiration Inhibition Test)
octamethylcyclotetrasiloxane	EC50	Toxicity > Water	3 h	activated sludge	ISO 8192 (Test for
556-67-2		solubility			Inhibition of Oxygen
					Consumption by Activated
					Sludge)

12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Isobornyl acrylate 5888-33-5	inherently biodegradable	aerobic	73,9 %	60 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Isobornyl acrylate 5888-33-5	not readily biodegradable.	aerobic	57 %	28 d	OECD Guideline 310 (Ready BiodegradabilityCO2 in Sealed Vessels (Headspace Test)
Dicyclopentyldimethylene diacrylate 42594-17-2	not readily biodegradable.	aerobic	28 %	28 day	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Ethyl phenyl(2,4,6- trimethylbenzoyl)phosphinate 84434-11-7		aerobic	< 10 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Phenyl bis(2,4,6- trimethylbenzoyl)-phosphine oxide 162881-26-7	not readily biodegradable.	aerobic	1 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Camphene 79-92-5	not readily biodegradable.	aerobic	78 %	28 day	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Camphene 79-92-5	inherently biodegradable	aerobic	78 %	28 day	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Dodecamethylcyclohexasiloxa ne 540-97-6	not readily biodegradable.	aerobic	4,47 %	28 d	OECD Guideline 310 (Ready BiodegradabilityCO2 in Sealed Vessels (Headspace Test)
Ethanone, 2,2-dimethoxy-1,2- diphenyl- 24650-42-8	not readily biodegradable.	aerobic	3 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
octamethylcyclotetrasiloxane 556-67-2	not readily biodegradable.	aerobic	3,7 %	29 d	OECD Guideline 310 (Ready BiodegradabilityCO2 in Sealed Vessels (Headspace Test)

12.3. Bioaccumulative potential

Hazardous substances CAS-No.	Bioconcentratio n factor (BCF)	Exposure time	Temperature	Species	Method
Isobornyl acrylate 5888-33-5	37	56 h	24 °C	Danio rerio	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)
Phenyl bis(2,4,6- trimethylbenzoyl)-phosphine oxide 162881-26-7	< 5				OECD Guideline 305 C (Bioaccumulation: Test for the Degree of Bioconcentration in Fish)
Dodecamethylcyclohexasiloxa ne 540-97-6	1.160	49 d		Pimephales promelas	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)
octamethylcyclotetrasiloxane 556-67-2	12.400	28 d		Pimephales promelas	EPA OTS 797.1520 (Fish Bioconcentration Test-Rainbow Trout)

12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
Isobornyl acrylate 5888-33-5	4,52		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Dicyclopentyldimethylene diacrylate 42594-17-2	4,6		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Ethyl phenyl(2,4,6- trimethylbenzoyl)phosphinate 84434-11-7	2,91	25 °C	EU Method A.8 (Partition Coefficient)
Phenyl bis(2,4,6- trimethylbenzoyl)-phosphine oxide 162881-26-7	5,8		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Camphene 79-92-5	4,35		not specified
Dodecamethylcyclohexasiloxa ne 540-97-6	8,87	23,6 °C	other guideline:
Ethanone, 2,2-dimethoxy-1,2- diphenyl- 24650-42-8	3,42		not specified
octamethylcyclotetrasiloxane 556-67-2	6,98	21,7 °C	other guideline:

12.5. Results of PBT and vPvB assessment

Hazardous substances	PBT / vPvB
CAS-No.	
Isobornyl acrylate	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
5888-33-5	Bioaccumulative (vPvB) criteria.
Dicyclopentyldimethylene diacrylate	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
42594-17-2	Bioaccumulative (vPvB) criteria.
Ethyl phenyl(2,4,6-	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
trimethylbenzoyl)phosphinate	Bioaccumulative (vPvB) criteria.
84434-11-7	
Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
oxide	Bioaccumulative (vPvB) criteria.
162881-26-7	
Camphene	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
79-92-5	Bioaccumulative (vPvB) criteria.
Titanium dioxide	According to Annex XIII of regulation (EC) 1907/2006 a PBT and vPvB assessment shall not
13463-67-7	be conducted for inorganic substances.
Dodecamethylcyclohexasiloxane	Fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
540-97-6	Bioaccumulative (vPvB) criteria.
Ethanone, 2,2-dimethoxy-1,2-diphenyl-	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
24650-42-8	Bioaccumulative (vPvB) criteria.
octamethylcyclotetrasiloxane	Fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
556-67-2	Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water. Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09* waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1.	UN number o	or ID number

ADR	3082
RID	3082
ADN	3082
IMDG	3082
IATA	3082

14.2. UN proper shipping name

ADR	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Isobornyl acrylate)
RID	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Isobornyl acrylate)
ADN	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Isobornyl acrylate)
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Isobornyl acrylate)
IATA	Environmentally hazardous substance, liquid, n.o.s. (Isobornyl acrylate)

14.3. Transport hazard class(es)

ADR	9
RID	9
ADN	9
IMDG	9
IATA	9

14.4. Packing group

ADR	III
RID	III
ADN	III
IMDG	III
IATA	III

14.5. Environmental hazards

not applicable
not applicable
not applicable
Marine pollutant
not applicable

14.6. Special precautions for user

ADR not applicable

	Tunnelcode:
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), A197 (IATA), 2.10.2.7 (IMDG) may be applied, which can result in a deviation from the transport classification for packed goods.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS	S) (Regulation (EC) No 1005/2009):	
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):		
Persistent organic pollutants (Regulation (EU) 2019/1021):		
VOC content	< 5 %	
(2010/75/EC)		

Not applicable Not applicable Not applicable

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

H226 Flammable liquid and vapour.

- H228 Flammable solid.
- H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer. H361f Suspected of damaging fertility.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very
	bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.